

# Alt-Pro

External plaster for smoothing outside walls (after cement is added) before the paint system is applied to receive a smooth and rich finish.

## Features:

Easy to apply and smooth. Sets quickly, easy to sand and leaves a smooth surface.

With Portland cement added, the product has good outside durability.

Cement must be added for outside use.

Internal walls may be smoothed without cement.

## Uses:

For filling and smoothing concrete walls, drywall, pre-cast construction, plaster and other walls.

## Technical Specifications:

**Product Code:** 725-500

**Hue:** Broken white (before concrete is added)

**Surface:** Matte

## Calculated Coating Ability:

Coating ability varies between 0.5 and 2.5 kg per sq meter according to the type of infrastructure.

**Dilution: While Painting:** Water      **Cleaning:** Soap and Water

**Setting Time:**    **Sanding Setting:** 3-4 hours    **Wait Between Coats:** 4 hours

**Shelf Life:** 12 Months

<b>Amount per Surface: Package Size</b>	<b>Amount per Surface</b>
25 kg	27

## Surface and Paint System Preparation

Clean the infrastructure of dust, oils, grease, etc. Remove pieces of metal, iron and piping and seal rough holes in the concrete. Seal holes over 0.5 mm with Tambourflex Filler Putty (Cat. # 737-454) and/or Tambourflex Flexible Putty (Cat.# 737-453). Add 20%-30% concrete to strengthen the Alt-Pro (add 6 kg concrete to Alt-Pro can).

It is recommended that the concrete be mixed with a bit of water before adding it to the Alt-Pro can.

If necessary, 10% water may be added to the plaster and cement mixture.

### **Recommended Paint System**

**Plaster:** the Alt-Pro may be applied via a special spraying device or trowel, at 1-2 kg per sq meter.

**Base coat:** one layer of Tambourflex Primer (737-000) diluted with 30% turpentine.

**Upper coat:** 2-3 coats of Supercryl MD, in 1200 different colors.

### **Tool Cleaning and Storage**

Clean work tools with water and soap immediately after finishing work. Pour thin layer of water on remaining paint and seal packaging against air. Store in covered and ventilated place.

### **Warnings and Safety Instructions:**

The paint is not to be eaten; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children Specific information regarding the product is available in the safety manual (MSDS).

### **General Notes:**

Do not apply when rain is expected and/or the wall temperature is under 10°C and the relative humidity is over 85%. Do not mix this product with products not recommended by us. Achieving desired results is contingent upon following all instructions concerning the proper application of the product. Prior to applying the product, the user must make sure that application of the product is in the intended manner and that the surface to be painted and its infrastructure have been properly prepared and match the product's intended application.

The information presented is based on knowledge and experience accumulated over the course of years. We reserve the right to update and/or change it at our discretion.