

ANTIQUE

Wall Paint for Unique Antique Appearance and Spectacular Authentic Texture

SPECIAL FEATURES

Creates an antique look in a range of vivid colors.

SUGGESTED USES

Interior decorative painting of concrete and gypsum walls and suitable wooden boards.

TECHNICAL DATA

Product code: 790-XXX
 Color: 12 colors tinted in the tinting machines
 Gloss: Matt
 Calculated spreading rate*: 10-12 sq.m/liter
 Recommended Thinner: **During application:** Water. **For cleaning:** Water and soap. **Once dry:** Acetone
 Drying Times: **Touch dry**:** 2-3 hours **Hard coat:** 24 - 48 hours **Hard coat for cleaning and washing:** 20 days after application
 Shelf life: 24 months
 Quantity per Pallet:

Package size	Quantity per Pallet
1 liters	576

SURFACE PREPARATION AND PAINT SYSTEM

Remove dust and grease thoroughly. Apply one coat of white/ colored **Supercryl** (according to the application instructions for Supercryl) and allow to dry.

APPLICATION REMARKS

Apply **Antique** paint using the **special brush** in short strokes to different directions. Apply on sections of 1-2 sq.m each. After 3-8 minutes (according to room temperature) press lightly on the paint, using the **special spatula**. Proceed to apply over the entire wall, paying attention to full coverage of the joints between the application sections, to avoid rough joints.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.