

BONDEROL SUPER

Bonding Primer to Reinforce the Substrate

SPECIAL FEATURES

Excellent penetration and adhesion to the substrate, fast drying, lead and chromates free.

SUGGESTED USES

Reinforce various interior substrates prior to application of acrylic topcoat paints (Supercryl, Supercryl More, Supercryl Easy, Emulsin, and more).

Substrate Types:

1. Limewash coats (up to 3 coats) or lime residue on a wall.
2. Polisid.
3. Joint Compound.

TECHNICAL DATA

Product code: 710-100
 Color: Transparent.
 Gloss: Eggshell
 Calculated spreading rate*: 6-7 sq.m/liter (in two coats)
 Recommended Thinner: **During application:** Not required. **For cleaning:** water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 2 hours
 Shelf life: 24 months
 Quantity per Pallet:

Package size	Quantity per Pallet
18 liters	27
5 liters	100
1 liter	576

SURFACE PREPARATION AND PAINT SYSTEM

Clean off dust, sand, grease and any other foreign matter. Remove any loose and peeling coats or excessively thick paint coats.

APPLICATION REMARKS

Stir the paint well before application and while painting.
 Apply using a brush/ Roller/ Regular spray or Airless spray.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.
 Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.
 Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.