

CALCIMO WHITE

SPECIAL FEATURES

Does not shrink upon drying. Easily sanded.

SUGGESTED USES

Fills and plugs static holes and cracks in interior concrete, plaster and other walls.

TECHNICAL DATA

Product code:	771-005	
Color:	White	
Gloss:	Matt	
Recommended Thinner:	During application: water. For cleaning: water and soap.	
Drying Times:	workable: For 2 hours. To be sand: after 2 hours	
Shelf life:	12 months	
Quantity per Pallet:	Package size	Quantity per Pallet
	6 kg	200

SURFACE PREPARATION AND PAINT SYSTEM

Remove dust, dirt and any other foreign matter. Pour water into a clean container. Scatter **Calcimo white** uniformly onto the water at a ratio of 2 parts powder for each part of water. Wait for about one minute before stirring, to prevent lumps. Stir for about one minute in the same direction. A ready to use paste is obtained.

APPLICATION REMARKS

The paste is workable for 90-120 minutes after its preparation. Fill the holes and the cracks with **Calcimo white** using a trowel. Once the place is dry, sand it with sandpaper.

CLEANING AND STORAGE

Clean work tools with water, immediately after use. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.