

EMULSIN

Water Based Acrylic Paint for Interior Walls

SPECIAL FEATURES

Easy, convenient application. Breathing paint, free of lead and chromates.

SUGGESTED USES

Painting interior plastered, concrete and brick ceilings and walls.

TECHNICAL DATA

Product code: 700-101
 Color: White.
 Gloss: Matt
 Calculated spreading rate*: 5-6 sq.m/liter (in two coats)
 Recommended Thinner: **During application:** Water. **For cleaning:** Water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 24 hours **Dry to recoat:** 3 hours
 Shelf life: 24 months
 Quantity per Pallet:

Package size	Quantity per Pallet
18 liters	27 ea

SURFACE PREPARATION AND PAINT SYSTEM

Interior Whitewashed surfaces

Remove any loose, flakey, peeling lime or excessively thick layers. Sand with sandpaper to a smooth surface. Clean off dust thoroughly. Apply one coat of **Bonderol Super Primer**. Allow drying to a hard coat and apply 2-3 coats of **Emulsin**.

Painted Interior Walls

Remove any old, loose and peeling paint and repair defects with **Calcimo X**. Smooth the surface using sandpaper. Apply 2-3 coats of **Emulsin**. When the old paint coat is intact and cannot be removed, apply 2-3 coats of **Emulsin** directly on it.

New, Unpainted, Plastered Interior Walls

Smooth the surface lightly using sandpaper. Remove dust and fill holes with **Calcimo X**. To obtain a smooth surface, apply a coat of **Tambourfill** and allow drying to a hard coat. Apply 2-3 coats of **Emulsin**.

Interior Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust and apply 2-3 coats of **Emulsin**.

APPLICATION REMARKS

Stir the paint well before application and while painting.

Apply using a brush/ Roller/ Airless: Dilute the paint with water for the first coat by 15% - 20% and stir well. Dilute the paint with water for the additional coats by 10%-15%. Apply 2-3 coats, according to the surface type.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.