

FANTASY- FAUX FINISHES

Water based acrylic paint that creates metallic look for application on acrylic painted interior walls.

SPECIAL FEATURES

Creates effects in 4 different finishes: gold, glitter, pearl and shimmer effect.
Easy to apply by sponge, spatula, brush, roller or piece of cloth.

SUGGESTED USES

Interior acrylic painted walls and unpainted wood.

TECHNICAL DATA

Product code: 795-501 Gold Luster, 795-502 Pearl Effect, 795-503 Glitter Effect, 795-504 Shimmer Effect
 Color: given by the background of the acrylic paint & 30 shades tinted in the mixing system
 Gloss: Matt-Satin
 Calculated spreading rate*: 20 sq/m/package of 0.75L
 Recommended Thinner: **During application:** Water. **For cleaning:** Water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Dry to recoat:** 3 hours. **Hard coat:** 24 hours.
 Shelf life: 24 months
 Quantity per Carton:

| | |
|---------------------|----------------------------|
| Package size | Quantity per Carton |
| 0.75 liter | 3 |

SURFACE PREPARATION AND PAINT SYSTEM

Apply two coats of **Supercryl** selecting in one of the 1000 shades (according to the application instructions for Supercryl) and allow drying.

Stir well the paint and apply **Fantasy** in thin layer using one of the tools: sponge, spatula, brush, roller or piece of cloth. Apply on sections of 1-2 sq.m each, paying attention to full coverage of the joints between the application sections, to avoid rough joints.

APPLICATION REMARKS

The **Fantasy** series can be applied in different styles that look like Stucco, marble, Fresko or cloth, and in a variety of effect that can be achieved by different tools and/or different ways of application. The Glitter effect looks like an emulsion, but once completely dry it gets transparent and glittering.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.