

**EMULSIONS**

**INDUSTRIAL  
PAINTS**

**ARCHITECTURAL  
PAINTS**

**SEALING &  
ADHESIVES**

**MARINE  
PAINTS**

**YOUR IMAGINATION...OUR PAINT.**



**[www.tambourpaints.com](http://www.tambourpaints.com) | [info@tambourpaints.com](mailto:info@tambourpaints.com)**

**PRINTING  
INKS**

**GYPSUM  
BOARDS**

**SPECIAL  
EFFECTS**

**BUILDING  
MATERIALS**

**MILITARY  
PAINTS**

# Tambour

*Your Imagination... Our paint.*



## Glow in the dark

[www.tambourpaints.com](http://www.tambourpaints.com)

# Glow in the Dark

- Water-based acrylic paint that glows in a green-blue shade in the dark.
- For application on coated based layer only.
- The paint glows for 2-8 hours depending on charging times and level of darkness.

# Glow in the Dark- Day Time



# Glow in the Dark- Night Time



# Glow in the Dark- Technical Information

**Water-based acrylic paint for interior walls, wood and metal that glows in the dark in a green-blue shade**

## **Technical data:**

Shade in day light: Yellow-Green

Shade in dark: Green- Blue

Gloss: Mat

Calculated coverage: 1 m<sup>2</sup>/l

Thinning: Water

Cleaning: Soap and water

Drying time: about 15 mn

Shelf life: 24 month

Package Size: 0.25 l.

# Glow in the Dark- Technical Information

## **Paint characteristics:**

The paint charges itself with exposure to day light and glow in the dark for 2 to 8 hours.

## **Paint use:**

Water-based acrylic paint for interior walls, ceilings, wood or metal to be used over acrylic painted walls.

## **General Guidelines:**

Apply two coats of acrylic paints on a chosen surface. Wait for complete drying (3 hours). It is recommended to apply Glow in the Dark on light colors. The lightest the background color, the stronger the effect will be.

# Glow in the Dark- Technical Information

## **Application:**

It is recommended to paint with a pattern. Tape the pattern to the surface you wish to adorn. Dip the tip of the provided brush in a little paint. Fill the pattern with a thick coat by tapping with the brush tip. After filling the pattern, remove carefully and clean immediately.

## **After application:**

After the paint has dried, expose it to a light source (daylight, neon, halogen, ordinary lamp) for at least 8 hours. The stronger the light source, the shorter the charging time will be and in result the duration of the glow will last longer. The thicker the coat of paint is applied the higher its glow capacity will be.

In the future if you would like to paint over the Glow in the Dark paint, lightly sand the paint off the wall, clean and then apply two coats of acrylic paint.

# Glow in the Dark- Technical Information

**Drying Time:** for contact – 15 minutes

## **Tools cleaning and storage:**

Clean the tools and pattern with water and soap immediately after the work is done. Firmly seal the packaging to prevent air infiltration. Store in a closed and properly ventilated space.

## **Warnings and precautions:**

**Safety Measures:**

Inedible. This paint is not defined as a hazardous material and does not contain materials requiring special marks or warnings. Safety data sheets for professional users are available upon request.

# Glow in the Dark- Technical Information

## General Remarks:

Do not apply the paint when rain is expected or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%.

Never mix this material with others when not specifically recommended by us. The desired results are obtained only through correct application of the product according to the application instructions.

The user must ensure, prior to application, that the recommended products are suitable to his requirements, method of application and environmental conditions and that the surface and its substrate are prepared properly.

Data presented here is based on our best knowledge and experience. We reserve the right to update or alter without prior notice.