

Great Quick Dry TS11

Synthetic coating paint, quick dry, silk-matte gloss.

PROPERTIES

Paint with extra quick dry that allows you to paint and transport in no time.

Suitable for spray, roller and brush painting.

SUGGESTED USES

Coating paint designed for painting on top of primer paint. For a quick and economic painting.

Designed to paint steel parts in a light industrial environment.

TECHNICAL DATA

Product code: 271-XXX

Color: White, red, blue, grey, black, yellow, green, silver

Gloss: Silk-matte

Calculated spreading rate (liter/m²): 8-11 m² / liter

Dilution: Spraying: 1-32 diluter, **Brushing:** 18 diluter.

Drying times: **Touch**:** One hour, **For holding :** 4-5 hours, **Final** :** 16 hours

Time between layers: 2 hours or more

Shelf life: 24 months.

Quantity for surface:	Container Size	Quantity for surface
	5 liters	100
	18 liters	27

SURFACE PREPARATION AND PAINT SYSTEM

Roughen the metal using grains until level Sa- 2.5 is reached. Should the surface preparation is not possible, mechanically roughen until reaching at least ST-2 level. Furthermore, remove all the grease and any other foreign matters.

APPLICATION REMARKS

Primer: For a quick painting process, it is recommended to use an Antirust as a primer paint. You can use the paint as a coating paint on top of all of Tambour's synthetic primers .

Painting:	Atm. Pressure	Nozzle diameter	Diluter	Percentage of dilution in volume
Brush/roller			18	10%
Normal spray	3-4		1-32	10-15%
Airless spray	3-4	15-21"	1-32	up to 5%

CLEANING AND STORAGE

Clean the tools with 1-32 diluter or 18 diluter. Close container well so that it is airtight. Store in a dark, well-ventilated place.

WARNINGS AND SAFETY INSTRUCTIONS

This product is to be applied and used in accordance with safety, health and environmental quality in Israel. Users must read the warnings and safety instructions in the material safety data sheet (MSDS), which is available from Tambour's safety department. Tel: 04-9877483, and on the product label. Keep away from fire and sparks. Non-edible. Make sure to provide adequate ventilation while working. Do not inhale fumes when spraying.

GENERAL COMMENTS

Do not paint when rain is expected in the next 72 hours and/or when temperatures are below 10°C and relative humidity is above 85%. When painting wood and metal infrastructures, make sure that the infrastructure being painted is completely dry. Never mix this material with materials not recommended by us. Achieving the desired results is subject to proper application of the product in strict conformance to our instructions. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted and their infrastructures have been properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

Synthetic paints' colors tend to change over time.

For further information feel free to call TELECOLOR - a free guidance calling line by Tambour: 1-800 -321-321

* Practical spreading rate can vary, depending on various causes: the surface, the application mode, the color, the painter's skill, and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** At 25°C and 65% relative humidity.

Manufactured by Tambour, certified ISO 9001 by the Standards Institution of Israel.