

# PAINT REMOVER

## Methyl-Bromide Based Paint Remover

### SPECIAL FEATURES

Is not absorbed by the substrate, therefore, does not reject the new paint.

### SUGGESTED USES

Soften and remove hard paints off concrete or plastered walls or wood and metal, without any damage to the substrate.

### TECHNICAL DATA

Product code: 688-001  
 Color: Greenish  
 Gloss: Matt.  
 Calculated spreading rate\*: 6 sq.m/liter (in one coat)  
 Recommended Thinner: **For cleaning:** Water and soap.  
 Drying Times: **Touch dry\*\*:** 1 hour. **Dry to recoat:** 5 hours  
 Shelf life: 12 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
1 liter	540
5 liters	135

### SURFACE PREPARATION AND PAINT SYSTEM

Used to prepare the surface prior to painting.

#### Any Substrate Type

Apply a generous coat of Tambour Paint Remover on the paint you wish to remove. Wait for 10-20 minutes for the paint to soften. Remove the soft paint off the substrate using a spatula. If stubborn paint remains, repeat the process. Upon removing all the old paint, wash the surface with water and soap. Once the surface is dry, smooth the surface with sandpaper, in preparation for the new paint. Gather all the removed paint and place it in the appropriate garbage bin.

### APPLICATION REMARKS

A ready to use product. Do not shake the container. Apply with a brush.

### CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Close the container tightly to prevent air penetration. Store in roofed and ventilated place.

### CAUTION

Inedible, highly flammable. Toxic upon contact with the skin or ingestion. Risk of severe, irreversible effects. Limited indication of cancerous effects. Inhalation and contact with skin and ingestion may cause irreversible damage. Keep in a locked cabinet, out of reach of children. Do not inhale the fumes. Do not empty into the drainage system. Wear appropriate cloths and protective gloves. Use in a well ventilated area only. In the event of insufficient ventilation, use appropriate breathing equipment. In the event of an accident, or when feeling ill, get medical aid immediately and present the packaging label. In the event of fumes inhalation, evacuate the injured person to a clean air area for resting. Do not shake the product. When opening the packaging, keep the cover away from your body, to prevent splashing. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

## GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.