

# Stucco – Mono Coat

**Acrylic top coat, with an Italian style marble imitation look. Provides a classic and elegant finish.**

- SPECIAL FEATURES:** Exceptional smooth and glossy texture.
- SUGGESTED USES:** For decorative finish of interior walls and surfaces (plaster, concrete, wood, etc.).
- TECHNICAL DATA:**
- Product Code:** 791-2XX
- Color:** White, Tambourmix shades spectrum and Viaro shades spectrum.
- Gloss:** Glossy, marble simulation
- Calculated spreading rate\*:** 0.3-4.0 kg/ m<sup>2</sup>
- Recommended Thinner:** **During Application:** Water      **Cleaning:** Water and soap.
- Drying Times:** **Touch dry\*\*:** 1/2 hour, **Hard coat:** 24 hours
- Shelf life:** 24 months
- Quantity per Pallet:**

<b>Package size</b>	<b>Quantity per Pallet</b>
5 kg.	100
20 kg	27

**SURFACE PREPARATION AND PAINT SYSTEM:**

**Plastered smoothed walls, plaster partitions, precast elements and concrete:**

Sandpaper the surface lightly. Remove dust, apply a coat of STARBOND and wait until completely dry. Apply a coat of BONDROL SUPER and wait until completely dry. Sandpaper lightly.

**Wooden surfaces:**

Apply a coat of Putty Adhesive 2000. Wait until completely dry and sandpaper lightly.

**Crumbly or powdery substrate:**

Apply a coat of BONDROL SUPER and wait until completely dry. Smooth the surface with STARBOND. Wait until completely dry and sandpaper lightly.

**Application Method:** The product is ready to use, without any dilution. If needed, dilute with a small quantity of water. Apply the Stucco with a stainless steel trowel or a

stainless steel float according to the desired final pattern. Apply in semi-circular movements (see the instruction leaflet), removing excess material in each move. Allow to dry for 1-2 hours.

When the Stucco is touch dry, use a clean stainless steel trowel to polish the Stucco and to obtain a marble-like finish ("ironing"/"stretching" movements).

The resulting final high gloss does not require any wax application. If any repairs are required, apply a thin coat even after the Stucco is completely dry, following the same instructions.

To protect the wall against stains, you may apply a coat of wax.

If at any future time you wish to paint over the Stucco, sandpaper the wall lightly until a smooth surface is obtained and apply two coats of SUPERCRYL 2000.

**TOOLS CLEANING AND STORAGE:** Clean work tools with soap and water immediately upon completing the application. Pour a thin layer of water on the remaining putty and close the container tightly to prevent air penetration. Store in a roofed, ventilated place.

**CAUTION:** Inedible. This product is not defined as hazardous and does not contain materials requiring special marking or warning. Keep away from children. Provide adequate ventilation of the work space during application. Read the specific information for this product in the Safety Data Sheet (MSDS).

**GENERAL COMMENTS:** Do not apply when rain is expected and or the temperature drops below 10°C and relative humidity exceeds 85%. Do not mix this product with products that are not recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* Practical spreading rate depends on several factors: The surface, the application mode, color shades, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

\*\* At 25°C and 65% relative humidity.

Produced by Tambour, authorized by the Israeli Institute of Standards, complying with ISO 9001.