

VARNIT DECK OIL WITH SPECIAL FORMULA

High quality deck oil with special formula for enhanced resistance to water penetration. A satin gloss clear oil that enables addition of a range of shades. Provides protection, fresh and decorative look to decks, wooden walls, furniture and wooden fences. Turpentine based.

SPECIAL FEATURES

Decks oil with exceptional clarity, maintains the look of the wood and adds gloss and bright color. Eases surface cleaning. Specifically adapted to the Israeli climate. High exterior resistance. Resists humidity and U.V. radiation. Contains an active anti-mold component. Very easy application. Suitable for all wood types.

SUGGESTED USES

Refresh decks, protect wood and enhance its look. Recommended for application on exterior wood surfaces, e.g., decks, around the house and the pool, garden furniture, casements, wooden fences and more.

TECHNICAL DATA

Product Code: 585-000 – clear base.

Color: Clear + 11 wood shading colors in Tambourmix system.

Gloss: Matt-satin.

Calculated spreading rate*: 10-20 sq.m/liter (in one coat depending on wood type and absorption)

Recommended Thinner During Application: Ready for use. **Cleaning:** Clean brush with Tambour Mineral Turpentine and then soap and water.

Drying Times: Touch dry**: 3-4 hours, **Hard coat:** 48 hours

Dry to recoat: 15 minutes (after the first coat is absorbed, do not wait for drying).

Shelf life: 24 months

Quantity per Pallet:	Package size	Quantity per Pallet:
	Quarter American Gallon	576
	American Gallon	100

SURFACE PREPARATION AND PAINT SYSTEM

New unpainted wood:

Sand the wood using sandpaper to remove the crust created by the plane, to allow optimal absorption and adhesion, then remove dust and grit. Or allow the wood to age slightly for 1-2 months and open its pores. For rough or scraped wood, apply the oil immediately upon installation.

Clean all dust, dirt and oil stains off the surface with **Varnit Cleaning Agent, Tambour Cat. No. 585-200** and rinse thoroughly. The surface must be clean of any dirt to ensure maximum absorption in the wood. Allow to dry for 2-3 days.

Notes:

A darker shade provides better protection. Do not apply over varnish. Completely remove all varnish first. ▪ It is recommended to test porosity, absorption and shade prior to application, on a hidden corner. Catalog shades may be slightly different in practice, depending on the type of the painted wood. It is recommended to construct the wood surface with a slope of one degree at least, to prevent water puddles.

PAINT APPLICATION:

Varnit Deck Oil is ready to use. Stir thoroughly before application right down to the bottom of the container and occasionally during application.

Apply a full coat of **Varnit Deck Oil** using a brush or a roller. Wait for 15 minutes after the first coat, and apply a second coat ("wet on wet") just before the first coat dries. Remove residue and wipe off any oil that was not fully absorbed by the wood. Allow to dry to a hard coat. **Varnit Deck Oil** protects the wood by penetration and provides protection and a rich look. It does not form a coat.

MAINTENANCE

Once the oil begins to disappear, clean the wood with **Varnit Cleaning Agent, Cat. No. 585-200** and rinse thoroughly to remove cleaning agent residue. Allow to dry. Apply one or two coats of **Varnit Deck Oil** to refresh the appearance of the wood and maintain its protection. Sanding is not required. It is recommended to renovate and refresh the deck once every six months at least.

TOOLS CLEANING AND STORAGE

Cleaning thinner: Turpentine. Clean tools with turpentine immediately after application is completed. Pour a thin layer of turpentine over the remaining oil and close the container tightly, to prevent air penetration. Store in a roofed, ventilated place.

CAUTION

Any work that includes application and use of this product shall be performed according to the applicable Safety, Health and Environmental regulations in Israel. Read the safety precautions and the warnings specified in the Safety Data Sheet (MSDS), available at Tambour Safety Department.

Telephone: 972-4-9877483 and indicated on the product's label. Keep away from fire and sparks. Inedible. Provide adequate ventilation of the work space. Do not inhale fumes when spraying.

GENERAL COMMENTS

Do not apply the paint when rain is expected within the next 72 hours and/or the deck is moist and/or when ambient temperature falls below 10 degrees Celsius and relative humidity exceeds 85%. For application on wood and metal substrates, verify that the substrate is completely dry. Never mix this material with others when not specifically recommended by us. The desired results are obtained only through correct application of the product according to the application instructions. The user must ensure, prior to application, that the products are designated for the intended use thereof and that the surface and substrate to be painted were properly prepared and are suitable for product application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

- * Practical spreading rate depends on several factors: The surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.
- ** At 25°C and 65% relative humidity.