

Silver Glitter – Paint Effects

A glittery silver/holographic look achieved by dry spraying silver/hologram glitter on wet paint. May be added to Glass Flakes or Glass Beads for an even more impressive effect.

Special Features:

Silver/hologram glitter coating. May be combined with Glass Flakes or Glass Beads at a recommended ratio of one 60 ml package of glitter for every 5 kg Glass Flakes/Beads.

Suggested Uses:

For application on indoor walls or ceilings, outside walls, public places: restaurants, hotels, clubs and more.

Technical Specifications:

Product Code: 795-570 **Hologram Glitter:** 795-571
Hue: Silver/Hologram
Surface: Shiny
Calculated Coating Ability*: 2-50 sq meter/kg (according to application and desired concentration)
Dilution: Dry spraying only.
Setting Time: **Dry to Touch **:** 1 hour **Hard Setting:** 24 hours **Wait between Coats:** 4 hours
Shelf Life: 60 Months
Amount per Surface:
Package Size: 60 milliliters

Surface and Paint System Preparation

Infrastructure must be smooth and straight. Bonderol Super must be applied to internal walls. Tambourflex bonding primer must be applied to outside walls according to the instructions on the packaging.

Application

May be sprayed dry directly on any paint so long as the paint is still wet. May be applied as additive to Glass Flakes or Beads – see appropriate technical manuals. May be mixed in clear lacquer and applied via brush/roller/spray.

Notes:

- Lighting is very important for the final result. Daylight or spotlights pointed directly at the wall will reflect multicolored light.
- The darker the selected background, the better the reflected light will look.
- Performing practice and test runs is recommended.

Tool Cleaning and Storage

Clean work tools with water and soap immediately after finishing work. Store in covered and ventilated place.

Warnings and Safety Instructions:

Do not eat. The product is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Keep out of reach of children! Put on protective goggles and mask before application. Cover floor with cardboard to prevent slippage. A professional safety manual is available upon request.

First Aid:

In the event of skin contact, wash with soap and water. In the event of eye contact remove particles from eye. Remove contact lenses if necessary. Wash with water for at least 15 minutes and seek medical attention. In case of swallowing particles seek medical attention.

Do not mix this product with other products not recommended by us. Achieving desired results is contingent upon following all instructions concerning the proper application of the product. Prior to applying the product, the user must make sure that application of the product is in the intended manner and that the surface to be painted and its infrastructure have been properly prepared and match the product's intended application. Our responsibility is for the quality of the product only.

General Notes:

The information presented is based on knowledge and experience accumulated over the course of years.

We reserve the right to update and/or change it at our discretion. Achieving desired results is contingent upon following all instructions concerning the proper application of the product. Prior to applying the product, the user must make sure that as application of the product is in the intended manner and that the surface to be painted and its infrastructure have been properly prepared and match the product's intended application.

* The actual coverage is contingent on several factors: the surface, the manner of painting, the color, the painter's expertise and on-site weather conditions. The assumption is that it consists of 75% of the calculated coverage capability.

** At 25°C and 65% relative humidity.