

# QUARTZ UNDERCOAT

A unique quartz undercoat for special effect paints, mineral plasters, etc., for inside or outside walls.

## PROPERTIES

An undercoat with a delicately roughened surface, ideal as a binder for applying special effect paints. It is an excellent binder between an inside acrylic undersurface and mineral products.

## APPLICATIONS

Suitable as an undercoat for special effect paints such as: **Antique, Fantasia, Suede, Super Wash**, Safari and others, also as a binder between an existing acrylic undersurface and a layer of mineral plaster. Inside the house. Suitable for covering black plaster, cement/concrete plaster, and painted walls. Applicable in both old and new houses.

## TECHNICAL DATA

Product code: 795-200  
 Shade: 1200 shades from the spectrum fan  
 Gloss: Matt  
 Texture: Finely roughened  
 Calculated spreading rate\*: 12 sq.m/liter in one layer  
 Dilution: May be diluted up to 40% with water  
 Drying Times: **Touch dry\*\***: 1-2 hours **Hard coat**: 24 hours (depending on weather conditions)  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
1 liters	576
5 liters	100

## SURFACE PREPARATION AND PAINT SYSTEM

**Painted walls:**  
 Before applying, remove all layers of loose and peeling material. Paint over repairs to concrete and plaster as required. Apply one or two layers of Quartz Undercoat, as is or colored.

**New walls:**  
 Apply white or colored Quartz Undercoat in 1-2 coats, wait till completely dry, and apply topcoat according to the instructions on the container..

## APPLICATION REMARKS

Undercoat: Apply with roller or brush, 1-2 coats of Quartz Undercoat, diluted up to 40%. The calculated hiding power is 12 sq.m/liter in one layer. Allow to dry for 4-6 hours.  
 Quartz Undercoat may be colored, according to the spectrum fan. Take care that the colored undercoat is of a shade close to the fan, even if not a perfect match.  
 Top application: According to the application instructions of the selected topcoat.

## CLEANING AND STORAGE

Clean all working tools with soap and water immediately after use. Pour a thin later of water over the surface of any paint left in the container, and close tightly to keep air out. Store in a cool, well-ventilated place.

## CAUTION

The paint is not edible. It is not designated as a dangerous material, and does not contain any substances requiring special marking or warning signs.  
 Full and precise information on this product is available on the product safety sheet (MSDS).

## GENERAL COMMENTS

Do not paint if rain is expected, and/or if the temperature of the walls is below 10°C, and Relative Humidity (R.H.) is above 85% Do not mix this material with other materials not recommended by us. To attain the best desired results, the product must be applied correctly, paying careful attention to instructions. Before use, the

user should make certain that the correct material has been selected for the purpose intended, and that the surface to be painted, and the under-surface, have been properly prepared for the application selected. The information provided here is based on many years' accumulated knowledge and experience. We reserve the right to update or to alter it without prior notice.

\* In practice, the hiding power depends on a number of factors: The nature of the surface, the method of applying the paint, the shade of the paint, the skill of the painter and the weather conditions at the site. The actual hiding power is usually taken to be about 75% of the calculated value.

\*\* At about 25°C and 65% Relative Humidity.  
"Green" label, 7 years' guarantee.