

SportCoat

Acrylic Paint for Tennis Court, Asphalt and Concrete.

Special Features:

An acrylic ,coloured coating designed to prevent skidding. Wear resistant and excellent exterior durability.Fills holes in asphalt surfaces and prevents their disintegration.

Suggested Uses:

Tennis court paint is a superior water-borne acrylic resin, specially produced for tennis courts, asphalt and concrete. It is also suitable for other similar sports surfaces.

Technical Data:

Product code: 753-020/753-010

Color: Dark green/Red

Calculated spreading rate*: In one coat- 2 Kg/m²

Recommended Thinner:

During Application: Water **for cleaning:** Water and soap

Drying Times: Touch dry:** 2 hours **Hard coat:** 7-10 days **Dry to recoat:** 4 hours

Shelf life: 12 months

Package size: 26 Kg

Quantity per pallet: 27

Surface Preparation and Paint System

Ensure all surfaces are clean, sound, dry and free from oil, grease, grime and other surface contaminants.

Asphalt: Thoroughly scrub with stiff broom and a suitable degreasing solution to remove dirt, oil and grease deposits, thoroughly rinse off with clean water and allow to dry. Apply 2 coats of Tennis Court Floor Paint.

Bare Concrete: Ensure dry. Surfaces should be cleaned by best available method to remove laitance, oils etc. and to "open up" substrate (eg Vacu-blast, disc grind, scable, acid etch, and hot compressed air treatment for deep oil removal). Apply 1 coat of Tennis Court Binder/Sealer to prepared surfaces. Apply 2 coats of Tennis Court Floor Paint.

Previously Painted: Perform adhesion check. If suspect - remove existing paint. If sound - wash, degrease and abrade. Apply Tennis Court Binder/Sealer to bare areas only. Apply 2 coats of SportCoat

Paint Application:

Dilute the paint with 5-10% water and stir well before application and while painting.

Not to be apply on a high temperature day and do not step prior to one week drying.

Cleaning and Storage:

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

Caution:

Inedible, keep out of reach children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop bellow 10⁰C and relative humidity is over 85%.

General comments:

Never mix this material with others when not specifically recommended by us. Achievement of the best desired result is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* Practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** at 25⁰C and 65% relative humidity.