

# SUPER WASH

## Unique Paint for Special Effect Creation on the Walls

### SPECIAL FEATURES

Semi transparent water paint applied on acrylic painted walls giving warmth of color, imitating an ancient fresco look. Easy to use, lead and chromates free.

### SUGGESTED USES

Interior decorative special effect painting of children rooms, bedrooms, living rooms and corridors.

### TECHNICAL DATA

Product code:	795-000
Color:	21 colors tinted by tambourmix
Gloss:	Matt
Calculated spreading rate*	40 sq.m/liter (in one coat)
Recommended Thinner:	Ready for use. To achieve brighter color thin with little water.
Drying Times:	<b>Touch dry**:</b> 15-20 minutes. <b>Hard coat:</b> 48 hours <b>Dry to recoat:</b> 1-2 hours
Shelf life:	24 months
Quantity per Pallet:	<b>Package size:</b> 0.5 liter

### SURFACE PREPARATION AND PAINT SYSTEM

De-grease old acrylic paint or apply one of Tambour premium acrylic emulsion paints. *Remember!* Select any desired shade from Tambour tinting system as long as it will be lighter than the selected **Super-Wash** shade.

#### Wipe-on Method for Wall:

Stir **Super-Wash** and pour into a shallow bowl or paint tray. Dip a wet soaked decorator sponge into **Super-Wash** and begin by 'washing' glaze over area starting in the top left hand corner and spread across using arc and circular movements. Keep the wet edge moving, completing a wall before stopping till achieving 'clouds' effects. A softener brush can be used simultaneously to smooth out sponge marks while wet. Wash tools with water immediately after use.

#### Additional Decorating Ideas/Applications:

Use **Super-Wash** for faux finishes as marbleizing, staining, texturing, combing, sponging, rag rolling and antiquing. While mixture is still wet, use texturing material (crumpled plastic wrap, sponge, etc.) to remove some color and create designs.

### CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

### CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

### GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.