

Super Coat

A high-coverage topcoat paint especially good for painting drywall.

Special Features:

Good bonding capabilities, breathes, excellent coverage capabilities, very white color, no lead or chromites.

Suggested Uses:

For internal painting of drywall, concrete brick and plaster.

Technical Specifications:

Product Code: 731-900

Color: White

Gloss: Matt

Calculated Coating Ability*: 7-8 sq meters/liter (two coats)

Recommended Thinner: Water **Cleaning:** Soap and Water

Drying Time: Dry to Touch **: One hour **Hard Setting:** 3 hours **Wait Between Coats:** 3 hours

Shelf Life: 24 Months

Amount per Surface:	Package Size	Amount per Surface
	15 Liters	27

Surface and Paint System Preparation

Whitewashed Internal Surfaces:

Remove all free, loose or peeling whitewash or overly thick layers. Sand until a smooth surface is attained. Clean away dust. If necessary, fill holes with **Calismo X**. Paint one coat of **Bonderol Super** and wait until fully dry. Apply two coats of **Super Coat**.

Indoor Surfaces Coated with Plastic-Based Paint:

Remove all old, loose and peeling paint. Where paint is peeling, apply coat of **Bonderol Super**. Smooth the surface with **Joint Compound** or **Glue Putty 2000** and paint over with coat of **Bonderol Super** and wait until dry. Apply two coats of **Super Coat**.

New Unpainted Internal Walls (Stucco):

Gently sand the internal surface. Remove dust and fill holes with **Calismo X**. In order to attain a smooth surface, paint a layer of **Tambourfill**, 20%-30% diluted, and wait until fully dry. Apply two coats of **Super Coat**.

Drywall:

Remove dust and prepare the wall for painting by closing the openings between the plaster units, using **Joint Compound** and a net for a uniform surface. Smooth the spackled surfaces with sandpaper. Clean off dust.

Apply coat of **Bonderol** over the **Joint Compound** before applying the **Super Coat**. Afterwards, apply 2-3 coats of **Super Coat**.

Painting Method

Stir the paint well before use and occasionally while painting.

Brush/roller/spray painting: dilute first coat with 15%-20% water and stir well. Dilute additional coats with 10%-15% water. Apply 2-3 coats according to the type of surface.

Tool Cleaning and Storage

Clean work tools with water and soap immediately after finishing work. Pour a thin layer of water on remaining paint and seal packaging against air. Store in covered and ventilated place.

Warnings and Safety Instructions:

The paint is not to be eaten; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Specific information regarding the product is available in the safety manual (MSDS).

General Notes:

Do not apply when rain is expected and/or the wall temperature is under 10°C and the relative humidity is over 85%. Do not mix this product with products not recommended by us. Achieving desired results is contingent on the proper application of the product while following all instructions. Prior to applying the product, the user must make sure that application of the product is in the intended manner and that the surface to be painted and its infrastructure have been properly prepared and match the product's intended application.

The information presented is based on knowledge and experience accumulated over the course of years. We reserve the right to update and/or change it at our discretion.

* The actual coating ability is based on several factors: the surface, the manner of painting, the hue, the painter's expertise and on-site weather conditions. The accepted assumption is that it consists of 75% of the calculated coating ability.

** At 25°C and 65% humidity.