

SUPERCRYL ONE COAT

High Quality Water Based Acrylic Paint Suitable for Supercryl One Coat Application

Special Features

Enables fast and easy application in one coat, washable, fast drying, breathing paint, lead and chromates free

Suggested Uses

Specially designed for frequent wall painting in children rooms, living rooms, bedrooms, corridors and balconies.

Technical Data

Code No.	731-501 White,
Colour	Snow white + 9 colours (see colour chart).
Gloss	Matt.
Calculated spreading rate*:	8 sqm/liter (in one coat)
Recommended Thinner	Water
Cleaning Thinner	Water and soap.
Touch dry **	1 hour
Hard dry **	3 hours
Dry to recoat **	3-4 hours
Shelf life **	24 months

Application Method

By Roller

Put the grid inside the can with its lower part immersed in the paint and its upper part leaning on the can side.

Immerse the roller directly into the oval can, without thinning. Remove excess paint with the grid and spread evenly in one thick coat. For excellent finish it is recommended to paint the wall until full coverage and then roll slightly in a crosswise motion.

By Brush or Pad

Thin with up to 15% water (3 glasses for one can).

Surface Preparation and Specification

Internal white washed surfaces lime

Remove loose or peeling material or too thick layers. Use sandpaper to reach a smooth surface. Clean off dust thoroughly. Apply Supercryl One Coat of **Bonderol Super** and allow 4 hours to dry. Apply Supercryl One Coat in one coat.

Internal walls painted with plastic paint

Remove loose or peeling material. Peeling areas should be painted with **Bonderol Super**. Smooth the surface until even with **Glue Putty 2000** or **Superbond**. Apply Supercryl One Coat of **Bonderol Super** and

allow 4 hours to dry. Apply Supercryl One Coat of **One Coat**. If the old paint is in good condition and cannot be removed. **Supercryl One Coat** may be applied directly.

External plaster and concrete surfaces

New well aged (at least 1 month after application plaster and concrete surfaces must be thoroughly cleaned from dust. Apply Supercryl One Coat of **Bonding Primer** thinned with 30% mineral spirit. After min. 24 hours apply one coat of Supercryl One Coat.

- In case the painting instructions are not fully applied, a second layer may be needed, especially on dark coloured walls.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.