

Material Safety Data Sheet
According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

1 Identification of substance:

- **Product details:**
- **Trade name:** *SYNTHETIC PAINT SATIN GLOSS FED 27857*
- **Article number:** 421-001 equal to military article number 6670-11124
- **Application of the substance / the preparation** *TOPCOAT*
- **Manufacturer/Supplier:** *TAMBOUR LTD.*
- **Further information obtainable from:** *Health & Safety*

2 Composition/Data on components:

- **Chemical characterization**
- **Description:** *Mixture of substances listed below with nonhazardous additions.*

· **Dangerous components:**

CAS: 64742-88-7 EINECS: 265-191-7	Solvent naphtha (petroleum), medium aliph. ☒ Xn; R 10-65	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix) ☒ Xn; R 10-20/21-38	10-25%
CAS: 78-83-1 EINECS: 201-148-0	iso-butanol ☒ Xi; R 10-37/38-67	1.0-2.5%

- **Additional information** *For the wording of the listed risk phrases refer to section 16.*

3 Hazard identification

- **Hazard description:** *not applicable*
- **Information concerning to particular hazards to man and environment**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
R 10 Flammable.
- **Classification system**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

4 First aid measures

- **After inhalation** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact** *Generally the product does not irritate the skin.*
- **After eye contact** *Rinse opened eye for several minutes under running water.*
- **After swallowing** *If symptoms persist consult doctor.*

Material Safety Data Sheet

According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

Trade name: SYNTHETIC PAINT SATIN
GLOSS FED 27857

(Contd. of page 1)

5 Fire fighting measures

- **Suitable extinguishing agents** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents**
Water.
Water with full jet.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

* 8 Exposure controls and personal protection gear

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene (mix)

OES	Short-term value: 662 mg/m ³ , 150 ppm
	Long-term value: 441 mg/m ³ , 100 ppm
	Sk

78-83-1 iso-butanol

OES	Short-term value: 231 mg/m ³ , 75 ppm
	Long-term value: 154 mg/m ³ , 50 ppm

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment**
- **General protective and hygienic measures** Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 3)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

Trade name: SYNTHETIC PAINT SATIN
GLOSS FED 27857

(Contd. of page 2)

· **Protection of hands:**



Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles.

9 Physical and chemical properties:

· **General Information**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· **Change in condition**

Melting point/Melting range:	undetermined
Boiling point/Boiling range:	137°C

· **Flash point:** 21 - 55°C

· **Ignition temperature:** 265.0°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.

· **Explosion limits:**

Lower:	0.6 Vol %
Upper:	7.0 Vol %

· **Vapour pressure at 20°C:** 6.7 hPa

· **Density:** Not determined

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix

(Contd. on page 4)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

Trade name: SYNTHETIC PAINT SATIN
GLOSS FED 27857

(Contd. of page 3)

· Solvent content:	
Organic solvents:	28.5 %
Water:	0.0 %
· Solids content:	
	71.5 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known
- **Dangerous decomposition products:** No dangerous decomposition products known

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

64742-88-7 Solvent naphtha (petroleum), medium aliph.

Oral	LD50	>6500 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

12 Ecological information:

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

GB

(Contd. on page 5)

Material Safety Data Sheet

According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

Trade name: **SYNTHETIC PAINT SATIN**
GLOSS FED 27857

(Contd. of page 4)

14 Transport information

· **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1993
- **Packaging group:** III
- **Hazard label** 3
- **Description of goods:** 1993 FLAMMABLE LIQUID, N.O.S. (not viscous) (XYLENES)

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1993
- **Label** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (XYLENES)

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1993
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** FLAMMABLE LIQUID, N.O.S. (XYLENES)

15 Regulations

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials

· **Risk phrases:**

10 Flammable.

· **Safety phrases:**

- 9 Keep container in a well-ventilated place.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 25 Avoid contact with eyes.
- 36/37 Wear suitable protective clothing and gloves.
- 51 Use only in well-ventilated areas.
- 60 This material and its container must be disposed of as hazardous waste.

(Contd. on page 6)

Material Safety Data Sheet
According to 91/155 EEC

Printing date 16.03.2004

Reviewed on 16.03.2010

Trade name: SYNTHETIC PAINT SATIN
GLOSS FED 27857

(Contd. of page 5)

- **Special labelling of certain preparations:**
Contains 2-butanone oxime. May produce an allergic reaction.

- **National regulations**

- **Technical instructions (air):**

Class	Share in %
I	0.3
NK	28.5

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information:

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

37/38 Irritating to respiratory system and skin.

38 Irritating to skin.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Tambour Ltd.- Health & Safety Department.

- **Contact:**

Haim Yahav

Phone: +972(4)987-7483

Fax: +972(4)985-3540

e-mail: h.yahav@tambour.co.il

- *** Data compared to the previous version altered.**