

# TOPSID

## Synthetic whitewash for painting internal walls of new buildings

### SPECIAL FEATURES

Economical, good covering power, does not wipe off like slaked lime, contains no lead or chromates. Not washable.

### SUGGESTED USES

For painting walls, ceilings, concrete and plaster internal surfaces in new buildings.

### TECHNICAL DATA

Product code: 736-200  
 Color: White  
 Gloss: Matt  
 Calculated spreading rate\*: 5-6 sq.m/liter (in two coats)  
 Recommended Thinner: **During application:** water. **For cleaning:** water and soap.  
 Drying Times: **Touch dry\*\*:** 1 hour. **Hard drying:** 3 hours **Time delay between applying layers:** 2 hours  
 Shelf life: 24 months  
 Quantity per Pallet:

Package size	Quantity per Pallet
18 liters	36

### SURFACE PREPARATION AND PAINT SYSTEM

#### New, unpainted Internal areas:

Smooth the entire surface with sandpaper to remove any lumps or granules and obtain a smooth, dust-free surface. Fill any holes or cracks with **Calcimo X**. When painting on new, smooth plaster, put on 1-2 undercoats of **Yad Rishonah** according to the quality of the surface. Allow to dry completely between coats. It is recommended to smooth the wall with sandpaper between coats, and after the second coat of **Yad Rishonah**. Put on 2-3 coats of **Topsid**.

#### Internal surfaces, previously whitewashed or painted with undercoats

Remove the loose, peeling layers of old whitewash. Smooth the entire surface with sandpaper to remove any lumps or granules and obtain a smooth, dust-free surface. Fill holes and cracks with **Clasimo X** and apply two coats of **Topsid**.

### APPLICATION REMARKS

Stir the paint well before use, and from time to time during painting.

**Painting with a roller or brush:** Dilute with 15%-25% water.

**Spray painting:** Dilute with up to 50% water.

### CLEANING AND STORAGE

Clean all working tools with soap and water immediately after use. Pour a thin layer of water over any paint left in the container, and close tightly to keep air out. Store in a cool, well-ventilated place.

### CAUTION

The paint is not edible. However, it is not designated as a dangerous material, and does not contain any substances requiring special marking or warning signs. Keep out of the reach of children. Make sure that any place where painting takes place is well ventilated.

Full and precise information on this product is available on the safety sheet (MSDS)

### GENERAL COMMENTS

Do not paint if rain is expected, and/or if air temperature is below 10°C and Relative Humidity (R.H.) is above 85% Do not mix these materials with other materials not recommended by us. For best results, the product must be applied correctly, paying careful attention to instructions. Before use, the user should make certain that the correct material has been selected for the purpose intended, and that the surface to be painted has been properly prepared for the application selected.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

\* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

\*\* at 25°C and 65% relative humidity.