

TAMBOURFILL

Walls Filling Primer

SPECIAL FEATURES

Excellent filling of plaster pores.

SUGGESTED USES

Filling and smoothing newly plastered walls (interior), prior to application of top acrylic paints (Supercryl 2000, Multicover, Emulsin, Supercryl and others) without using Bonderol Super Primer to reinforce the surface.

TECHNICAL DATA

Product code: 719-004
 Color: Off-White
 Gloss: Matt
 Calculated spreading rate*: 4-5 sq.m/liter (in one coat)
 Recommended Thinner: **During application:** Water. **For cleaning:** Water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 4 hours **Dry to recoat:** 2-4 hours
 Shelf life: 2 4 months
 Quantity per Pallet:

Package size	Quantity per Pallet
5 liters	125
18 liters	27

SURFACE PREPARATION AND PAINT SYSTEM

Smooth the surface lightly with sandpaper. Remove dust and plaster spray. Fill holes with **Calcimo X**. Apply a first coat of **Tambourfill** and allow drying to a dry coat. When required (if the substrate filling is insufficient) sand lightly and apply a second coat of **Tambourfill**. Allow drying to a hard coat and apply a topcoat.

APPLICATION REMARKS

Stir the paint well before painting and during application.
 Brush/ Roller/ Spray and Airless spray application diluted up to 10% with water.

CLEANING AND STORAGE

Clean work tools with water and soap, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us. Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application. Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site.

Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.