

TAMBOURTEX 55

Fine Textured Decorative Coating

SPECIAL FEATURES

The fine texture provides a unique decorative coating.

SUGGESTED USES

Coating interior plastered cement and brick walls.

TECHNICAL DATA

Product code: 716-055
 Color: White
 Gloss: Matt
 Calculated spreading rate*: 1 – 2.5 kg/sq.m (in one coat).
 Recommended Thinner: **During application:** water (up to 15%). **For cleaning:** water and soap.
 Drying Times: **Touch dry**:** 1 hour. **Hard coat:** 2-4 hours **Dry to recoat:** 3 hours
 Shelf life: 24 months
 Quantity per Pallet:

Package size	Quantity per Pallet
7 kg	100
15 kg	44
28 kg	27

SURFACE PREPARATION AND PAINT SYSTEM

Internal Whitewashed surfaces

Remove any lime and lime residue thoroughly. Apply one coat of **Bonderol Super Primer** and allow drying to a hard coat. Apply a first coat of **Supercryl** (white) diluted with water by 20%. Allow drying to a hard coat. Apply **Tambourtex 55**, in one of the application methods specified below.

Painted Interior Walls

When the existing paint is **Supercryl**, you may apply paint directly over it, provided that it is well adhered to the plaster and shows no signs of peeling. When the existing paint is not **Supercryl**, remove any old paint, lime and residue thoroughly. Apply one coat of **Bonderol Super Primer** and allow drying to a hard coat. Apply a first coat of **Supercryl** (white) diluted with water by 20%. Allow drying to a hard coat. Apply **Tambourtex 55**, in one of the application methods specified below.

Interior Unpainted Concrete and Cement Plaster Surfaces

Paint can be applied only after the plaster is completely cured (one month or more after application). Remove dust, grease, dirt and any other foreign matter. Apply a first coat of **Supercryl** (white) diluted with water by 20%. Allow drying to a hard coat. Apply **Tambourtex 55**, in one of the application methods specified below.

APPLICATION REMARKS

Stir the paint well before application.

Spray Application: Spray a uniform coat of **Tambourtex 55**, allow to dry for 2-3 hours and apply a second, uniform coat of **Tambourtex 55** when the spreading is not consecutive.

Roller Application: Apply **Tambourtex 55** using a brush/ trowel/ spatula and then crisscross with the roller.

CLEANING AND STORAGE

Clean work tools with soap and water, immediately after use. Pour a thin layer of water on the remaining paint and close the container tightly to prevent air penetration. Store in a roofed and ventilated place.

CAUTION

Inedible, keep out of reach of children. Use in a well ventilated area only. Do not apply when rain is expected or when temperatures drop below 10°C and relative humidity is over 85%.

GENERAL COMMENTS

Never mix this material with others when not specifically recommended by us.

Achievement of the best desired results is subject to proper application in strict conformance to our instructions and safety measures. Before application, the user should verify that the product is indeed designed for the intended usage and that the surfaces to be painted are properly prepared, and are suitable for the product's application.

Data presented here is based on our best knowledge and experience. We reserve the right to update and/or alter it without prior notice.

* practical spreading rate can vary, depending on the surface, the application mode, the painter's skill and weather conditions at the site. Assume approximately 75% of the calculated spreading rate.

** at 25°C and 65% relative humidity.