

# Water-Based Bonding Primer

**A white primer based on acrylic resins providing excellent bonding for the topcoat.**

## Features:

The primer is based on a nano acrylic emulsion providing excellent penetration into walls and allowing long-term durability of alkali substances.

## Uses:

Suitable for painting outside walls and may also be used as a primer for acrylic paints such as Supercryl MD, Acrylic 1945, etc. for painting outer walls.

## Technical Specifications:

<b>Product Code:</b>	783-090	
<b>Type of Paint:</b>	Primer	
<b>Colour:</b>	White	
<b>Based on:</b>	Acrylic emulsion	
<b>Surface:</b>	Matt	
<b>Texture:</b>	Smooth seal	
<b>Calculated Coating Ability*:</b>	6-8 sq meters/liter (depending on infrastructure absorption)	
<b>Dilution:Water</b>	<b>Cleaning:</b>	Soap and Water
<b>Setting Time: Dry to Touch **:</b>	1 hour	<b>Hard Setting:</b> 3 hours <b>Between Layers:</b> 4 hours
<b>Shelf Life:</b>	24 months	
<b>Amount per Surface:</b>	<b>Package Size</b>	<b>Amount per Surface</b>
	18 liter	27

## Surface and Paint System Preparation

Before application, remove loose layers and wash well with sweet water jet at 120 atmospheres.

Perform concrete and plaster repairs as needed.

New concrete – wait at least 28 days for curing.

## Application

Stir the paint until uniform.

**Via roller** – dilute with 25% water, at most.

**Via airless spraying** – dilute with 25% water, at most.

The primer must be applied via spraying or rolling, diluted with up to 25% water, at a rate of 6-8 sq meters per liter, depending on the wall's absorption qualities. After drying for 3 hours, the Tamborflex system may be applied at the desired texture, depending on the type of crack and desired finish.

## Warnings

Under no circumstances should this product be mixed with materials not recommended by us. Do not apply when the outdoor temperature is under 10°C and the relative humidity is over 85%. Keep out of reach of children. Work area must be properly ventilated. Eyes and skin must be protected during use. After painting, wash hands with water and soap. Avoid inhaling the product and its fumes.

## Tool Cleaning and Storage

After opening, pour thin layer of water on remaining paint, close carefully and store in shade.

## Warnings and Safety Instructions:

The paint is not to be eaten; the paint is not defined as a dangerous substance and does not contain materials requiring special markings or warnings. Specific information regarding the product is available in the safety manual (MSDS).

## General Notes:

The information presented is based on knowledge and experience accumulated over the course of years.

We reserve the right to update and/or change it at our discretion.

Our recommendations should not be considered product guarantees. Prior to use, the user must ensure that the product is appropriate to his requirements, application methods and environmental conditions.

For further information, contact our technical service department.

\* The actual coverage is contingent on several factors: the surface, the manner of painting, the color, the painter's expertise and on-site weather conditions. The assumption is that it consists of 75% of the calculated coverage capability.

\*\* At 25°C and 65% relative humidity.